



FAG

**WS22213-E1-XL-K-2RSR**

Spherical Roller Bearing

Spherical roller bearing WS222..-E1-XL-K-2RSR, symmetric with cage guidance ring

X-life

## Technical information




## Your current product variant

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	JPA	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	
Sealing	2RSR	Seals on both sides, normal temperature
Sealing - excess width	WS	Sealing - excess width

## Main Dimensions &amp; Performance Data

d	65 mm	Bore diameter
D	120 mm	Outside diameter
B	38 mm	Width
C <sub>r</sub>	202.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	210.000 N	Basic static load rating, radial
C <sub>ur</sub>	26.500 N	Fatigue load limit, radial
n <sub>G</sub>	1.740 1/min	Limiting speed
≈m	1,687 kg	Weight





### Mounting dimensions

$d_{a \min}$	76,2 mm	Minimum diameter shaft shoulder
$d_{a \max}$	76,2 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	111 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum recess radius
$d_{b \min}$	70 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	8 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$D_1$	110,2 mm	Bore diameter outer ring
$d_2$	76,2 mm	Raceway diameter of the inner ring
$d_s$	3,2 mm	Diameter lubrication hole
$n_s$	6,5 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$e$	0,24	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,81	Dynamic axial load factor
$Y_2$	4,19	Dynamic axial load factor
$Y_0$	2,75	Static axial load factor

### Additional information

H2213-T-WS	Adapter sleeve
AH2213-WS	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment
-  Dynamic angular error and misalignment