

**RNA4902-XL**

Radial roller bearing

Radial roller bearing RNA..-XL

X-life

Technical information



Your current product variant

| | | |
|------------------|----------|-------------------|
| Cage | Standard | |
| Lubrication hole | With | With |
| Coating | Without | |
| Type of Seal | Without | |
| Special features | Without | |
| Number of rows | 1 | Single-row design |

Main Dimensions & Performance Data

| | | |
|-----------------|--------------|---------------------------------------|
| F_w | 20 mm | Under roller diameter |
| D | 28 mm | Outside diameter |
| B | 13 mm | Width |
| C_r | 12.000 N | Basic dynamic load rating, radial |
| C_{0r} | 13.600 N | Basic static load rating, radial |
| C_{ur} | 2.470 N | Fatigue load limit, radial |
| n_G | 21.100 1/min | Limiting speed |
| $n_{G, Grease}$ | 12.600 1/min | Limiting speed for grease lubrication |
| n_{gr} | 12.000 1/min | Reference speed |
| $\approx m$ | 21,9 g | Weight |



Dimensions

| | | |
|-----------|--------|---------------------------|
| r_{min} | 0,3 mm | Minimum chamfer dimension |
| C | 13 mm | Width, outer ring |






Temperature range

| | | |
|-----------|--------|----------------------------|
| T_{min} | -30 °C | Operating temperature min. |
| T_{max} | 120 °C | Operating temperature max. |

Additional information

| | |
|-----------|----------------|
| G20X28X4 | Sealing ring |
| SD20X28X4 | Sealing ring 2 |

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope