

**RNA6903-XL**

Radial roller bearing

Radial roller bearing RNA..-XL

X-life

Technical information



Your current product variant

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Sealing	Without	
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F_w	22 mm	Under roller diameter
D	30 mm	Outside diameter
B	23 mm	Width
C_r	21.100 N	Basic dynamic load rating, radial
C_{0r}	29.000 N	Basic static load rating, radial
C_{ur}	5.200 N	Fatigue load limit, radial
n_G	20.000 1/min	Limiting speed
n_G Grease	12.000 1/min	Limiting speed for grease lubrication
n_{gr}	10.500 1/min	Reference speed
m	0,043 kg	Weight



Dimensions

r_{\min}	0,3 mm	Minimum chamfer dimension
C	23 mm	Width, outer ring






Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

G22X30X4	Sealing ring
SD22X30X4	Sealing ring 2

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope