


RNA6908-ZW-XL [↗](#)

Radial roller bearing

Needle roller bearings RNA69...-ZW,
Dimension series 69, double row

X-life

Technical information



Your current product variant

Cage	Standard	
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Lubrication hole	With	With
Coating	Without	
Lubricant	Without	
Type of Seal	Without	
Special features	Without	
Number of rows	ZW	Double-row design



Main Dimensions & Performance Data

F_w	48 mm	Under roller diameter
D	62 mm	Outside diameter
C_r	74.000 N	Basic dynamic load rating, radial
C_{0r}	116.000 N	Basic static load rating, radial
C_{ur}	19.800 N	Fatigue load limit, radial
n_G	9.200 1/min	Limiting speed
n_G Grease	5.500 1/min	Limiting speed for grease lubrication
n_{gr}	5.400 1/min	Reference speed
m	260,54 g	Weight






Dimensions

r_{min}	0,6 mm	Minimum chamfer dimension
C	40 mm	Width, outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Small design envelope