

**FAG****51138-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 511...-MP,
single direction, solid brass cage

Technical information

**Your current product variant**

| | | |
|----------------------------------|----|--|
| Cage | MP | Solid brass cage, rolling element guided |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|----------------------------------|
| d | 190 mm | Inner diameter shaft washer |
| D | 240 mm | Outer diameter housing washer |
| T | 37 mm | Height |
| C _a | 161.000 N | Basic dynamic load rating, axial |
| C _{0a} | 650.000 N | Basic static load rating, axial |
| C _{ua} | 20.200 N | Fatigue load limit, axial |
| n _G | 2.040 1/min | Limiting speed |
| n _{gr} | 1.850 1/min | Reference speed |
| m | 4,06 kg | Weight |

Mounting dimensions

| | | |
|--------------------|--------|--------------------------------------|
| d _{a min} | 220 mm | Minimum diameter shaft shoulder |
| D _{a max} | 210 mm | Maximum diameter of housing shoulder |
| r _{a max} | 1 mm | Maximum filled radius |



Dimensions

| | | |
|-----------|--------|-------------------------------|
| r_{min} | 1,1 mm | Minimum chamfer dimension |
| D_1 | 193 mm | Inner diameter housing washer |
| d_1 | 237 mm | Outer diameter shaft washer |





Temperature range

| | | |
|-----------|--------|----------------------------|
| T_{min} | -30 °C | Operating temperature min. |
| T_{max} | 150 °C | Operating temperature max. |

Calculation factors

| | | |
|---|-----|---------------------|
| A | 2,3 | Minimum load factor |
|---|-----|---------------------|

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed