

**FAG****51168-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 511..-MP,
single direction, solid brass cage

Technical information

**Your current product variant**

| | | |
|----------------------------------|----|--|
| Cage | MP | Solid brass cage, rolling element guided |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Dimensional / heat stabilization | S1 | Rings dimensional stabilized up to 200° |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|----------------------------------|
| d | 340 mm | Inner diameter shaft washer |
| D | 420 mm | Outer diameter housing washer |
| T | 64 mm | Height |
| C _a | 380.000 N | Basic dynamic load rating, axial |
| C _{0a} | 1.810.000 N | Basic static load rating, axial |
| C _{ua} | 51.000 N | Fatigue load limit, axial |
| n _G | 1.160 1/min | Limiting speed |
| n _{gr} | 1.020 1/min | Reference speed |
| m | 19,9 kg | Weight |

Mounting dimensions

| | | |
|--------------------|--------|--------------------------------------|
| d _{a min} | 388 mm | Minimum diameter shaft shoulder |
| D _{a max} | 372 mm | Maximum diameter of housing shoulder |
| r _{a max} | 2 mm | Maximum filled radius |



Dimensions

| | | |
|-----------|--------|-------------------------------|
| r_{min} | 2 mm | Minimum chamfer dimension |
| D_1 | 344 mm | Inner diameter housing washer |
| d_1 | 416 mm | Outer diameter shaft washer |






Temperature range

| | | |
|-----------|--------|----------------------------|
| T_{min} | -30 °C | Operating temperature min. |
| T_{max} | 200 °C | Operating temperature max. |

Calculation factors

| | | |
|---|----|---------------------|
| A | 18 | Minimum load factor |
|---|----|---------------------|

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing