

**FAG****51176-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 511..-MP,
single direction, solid brass cage

Technical information

**Your current product variant**

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	380 mm	Inner diameter shaft washer
D	460 mm	Outer diameter housing washer
T	65 mm	Height
C _a	430.000 N	Basic dynamic load rating, axial
C _{0a}	2.230.000 N	Basic static load rating, axial
C _{ua}	50.000 N	Fatigue load limit, axial
n _G	1.070 1/min	Limiting speed
n _{gr}	860 1/min	Reference speed
m	21,84 kg	Weight

Mounting dimensions

d _{a min}	428 mm	Minimum diameter shaft shoulder
D _{a max}	412 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum fillet radius



Dimensions

r_{min}	2 mm	Minimum chamfer dimension
D_1	384 mm	Inner diameter housing washer
d_1	456 mm	Outer diameter shaft washer






Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

A	25	Minimum load factor
---	----	---------------------

Characteristics

-  F_a Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing