

**FAG****51211**

Axial deep groove ball bearing

Axial deep groove ball bearing 512, single direction, steel sheet metal cage

Technical information

**Your current product variant**

| | | |
|----------------------------------|----|---|
| Cage | JP | Steel sheet metal |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|----------------------------------|
| d | 55 mm | Inner diameter shaft washer |
| D | 90 mm | Outer diameter housing washer |
| T | 25 mm | Height |
| C _a | 58.000 N | Basic dynamic load rating, axial |
| C _{0a} | 133.000 N | Basic static load rating, axial |
| C _{ua} | 6.000 N | Fatigue load limit, axial |
| n _G | 4.350 1/min | Limiting speed |
| n _{gr} | 5.700 1/min | Reference speed |
| m | 0,557 kg | Weight |

Mounting dimensions

| | | |
|--------------------|-------|--------------------------------------|
| d _{a min} | 76 mm | Minimum diameter shaft shoulder |
| D _{a max} | 69 mm | Maximum diameter of housing shoulder |
| r _{a max} | 1 mm | Maximum fillet radius |



Dimensions

| | | |
|------------|-------|-------------------------------|
| r_{\min} | 1 mm | Minimum chamfer dimension |
| D_1 | 57 mm | Inner diameter housing washer |
| d_1 | 90 mm | Outer diameter shaft washer |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 150 °C | Operating temperature max. |

Calculation factors

| | | |
|---|------|---------------------|
| A | 0,11 | Minimum load factor |
|---|------|---------------------|

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed