

**FAG****51336-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 513...MP,
single direction, solid brass cage

Technical information



Your current product variant

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	180 mm	Inner diameter shaft washer
D	300 mm	Outer diameter housing washer
T	95 mm	Height
C _a	520.000 N	Basic dynamic load rating, axial
C _{0a}	1.830.000 N	Basic static load rating, axial
C _{ua}	54.000 N	Fatigue load limit, axial
n _G	1.130 1/min	Limiting speed
n _{gr}	2.000 1/min	Reference speed
m	28 kg	Weight

Mounting dimensions

d _{a min}	252 mm	Minimum diameter shaft shoulder
D _{a max}	228 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum filled radius



Dimensions

r_{min}	3 mm	Minimum chamfer dimension
D_1	184 mm	Inner diameter housing washer
d_1	295 mm	Outer diameter shaft washer

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

A	18	Minimum load factor
---	----	---------------------

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed