

**FAG****53202**

## Axial deep groove ball bearing

Axial deep groove ball bearing 532, single direction, with spherical housing washer, steel sheet metal cage

## Technical information



## Your current product variant

Cage	JP	Steel sheet metal
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

## Main Dimensions &amp; Performance Data

d	15 mm	Inner diameter shaft washer
D	32 mm	Outer diameter housing washer
T	13,3 mm	Height
$C_a$	16.600 N	Basic dynamic load rating, axial
$C_{0a}$	24.800 N	Basic static load rating, axial
$C_{ua}$	1.130 N	Fatigue load limit, axial
$n_G$	9.800 1/min	Limiting speed
$n_{gr}$	14.300 1/min	Reference speed
$\approx m$	0,033 kg	Weight

## Mounting dimensions

$d_{a \min}$	25 mm	Minimum diameter shaft shoulder
$D_{a \max}$	24 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum filled radius



## Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$D_1$	17 mm	Inner diameter housing washer
$d_1$	32 mm	Outer diameter shaft washer
R	28 mm	Radius spherical housing washer
A	12 mm	Distance of the center point
$T_1$	15 mm	Height with seat washer
$D_2$	24 mm	Bore diameter seat washer
$D_3$	35 mm	Outside diameter seat washer
C	4 mm	Height seat washer

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

## Calculation factors

A	0,003	Minimum load factor
---	-------	---------------------

## Additional information

U202	Seat washer
------	-------------

## Characteristics

$F_a$	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment