



**FAG****53232-MP**

## Axial deep groove ball bearing

Axial deep groove ball bearing 532...-MP, single direction, with spherical housing washer, solid brass cage

## Technical information



## Your current product variant

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

## Main Dimensions &amp; Performance Data

d	160 mm	Inner diameter shaft washer
D	225 mm	Outer diameter housing washer
T	54,7 mm	Height
C <sub>a</sub>	240.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	770.000 N	Basic static load rating, axial
C <sub>ua</sub>	25.500 N	Fatigue load limit, axial
n <sub>G</sub>	1.900 1/min	Limiting speed
n <sub>gr</sub>	2.350 1/min	Reference speed
≈m	6,315 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	199 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	190 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1,5 mm	Maximum filled radius



## Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$D_1$	163 mm	Inner diameter housing washer
$d_1$	222 mm	Outer diameter shaft washer
R	160 mm	Radius spherical housing washer
A	74 mm	Distance of the center point
$T_1$	61 mm	Height with seat washer
$D_2$	190 mm	Bore diameter seat washer
$D_3$	235 mm	Outside diameter seat washer
C	21 mm	Height seat washer

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

## Calculation factors

A	3,2	Minimum load factor
---	-----	---------------------

## Additional information

U232	Seat washer
------	-------------

## Characteristics

	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment