

**FAG****53305**

## Axial deep groove ball bearing

Axial deep groove ball bearing 533, single direction, with spherical housing washer, steel sheet metal cage

## Technical information



## Your current product variant

Cage	JP	Steel sheet metal
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

## Main Dimensions &amp; Performance Data

d	25 mm	Inner diameter shaft washer
D	52 mm	Outer diameter housing washer
T	19,8 mm	Height
$C_a$	34.500 N	Basic dynamic load rating, axial
$C_{0a}$	55.000 N	Basic static load rating, axial
$C_{ua}$	2.500 N	Fatigue load limit, axial
$n_G$	6.000 1/min	Limiting speed
$n_{gr}$	10.400 1/min	Reference speed
$\approx m$	0,175 kg	Weight

## Mounting dimensions

$d_{a \min}$	41 mm	Minimum diameter shaft shoulder
$D_{a \max}$	38 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum filled radius



## Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	27 mm	Inner diameter housing washer
$d_1$	52 mm	Outer diameter shaft washer
R	45 mm	Radius spherical housing washer
A	21 mm	Distance of the center point
$T_1$	22 mm	Height with seat washer
$D_2$	38 mm	Bore diameter seat washer
$D_3$	55 mm	Outside diameter seat washer
C	6 mm	Height seat washer

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

## Calculation factors

A	0,019	Minimum load factor
---	-------	---------------------

## Additional information

U305	Seat washer
------	-------------

## Characteristics

$F_a$	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment