

**FAG****591/630-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 591...-MP, double direction, with spherical housing washer, solid brass cage

Technical information



Your current product variant

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	630 mm	Inner diameter shaft washer
D	750 mm	Outer diameter housing washer
T	73 mm	Height
C _a	560.000 N	Basic dynamic load rating, axial
C _{0a}	3.750.000 N	Basic static load rating, axial
C _{ua}	66.000 N	Fatigue load limit, axial
n _G	690 1/min	Limiting speed
n _{gr}	520 1/min	Reference speed
m	61,6 kg	Weight

Mounting dimensions

d _{a min}	701 mm	Minimum diameter shaft shoulder
D _{a max}	680 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum filled radius



Dimensions

r_{min}	3 mm	Minimum chamfer dimension
D_1	635 mm	Inner diameter housing washer
d_1	745 mm	Outer diameter shaft washer







Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

A	82	Minimum load factor
---	----	---------------------

Characteristics

-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing