

**FAG****591/630-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 591...-MP, double direction, with spherical housing washer, solid brass cage

Technical information



Your current product variant

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	630 mm	Inner diameter shaft washer
D	750 mm	Outer diameter housing washer
T	73 mm	Height
C _a	560.000 N	Basic dynamic load rating, axial
C _{0a}	3.750.000 N	Basic static load rating, axial
C _{ua}	66.000 N	Fatigue load limit, axial
n _G	690 1/min	Limiting speed
n _{gr}	520 1/min	Reference speed
m	61,6 kg	Weight

Mounting dimensions

d _{a min}	701 mm	Minimum diameter shaft shoulder
D _{a max}	680 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum filled radius



Dimensions

r_{min}	3 mm	Minimum chamfer dimension
D_1	635 mm	Inner diameter housing washer
d_1	745 mm	Outer diameter shaft washer







Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

A	82	Minimum load factor
---	----	---------------------

Characteristics

-  F_a Axial load in one direction
-  F_a Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing