

**FAG****52202**

Axial deep groove ball bearing

Axial deep groove ball bearing 522, double direction, steel sheet metal cage

Technical information

**Your current product variant**

Cage	JP	Steel sheet metal
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	10 mm	Inner diameter shaft washer
D	32 mm	Outer diameter housing washer
T ₂	22 mm	Height
C _a	16.600 N	Basic dynamic load rating, axial
C _{0a}	24.800 N	Basic static load rating, axial
C _{ua}	1.130 N	Fatigue load limit, axial
n _G	9.800 1/min	Limiting speed
n _{gr}	13.700 1/min	Reference speed
m	85 g	Weight

Mounting dimensions

d _{a max}	15 mm	Maximum diameter shaft shoulder
D _{a max}	22 mm	Maximum diameter of housing shoulder
r _{a max}	0,6 mm	Maximum filled radius
r _{a1 max}	0,3 mm	Maximum filled radius



Dimensions

D ₁	17 mm	Inner diameter housing washer
B	5 mm	Height shaft washer
r _{min}	0,6 mm	Minimum chamfer dimension
r _{1 min}	0,3 mm	Minimum chamfer dimension






Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Calculation factors

A	0,003	Minimum load factor
---	-------	---------------------

Characteristics

-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed