

**FAG****52328-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 523...MP,
double direction, solid brass cage

Technical information

**Your current product variant**

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	120 mm	Inner diameter shaft washer
D	240 mm	Outer diameter housing washer
T ₂	140 mm	Height
C _a	385.000 N	Basic dynamic load rating, axial
C _{0a}	1.240.000 N	Basic static load rating, axial
C _{ua}	41.000 N	Fatigue load limit, axial
n _G	1.360 1/min	Limiting speed
n _{gr}	2.550 1/min	Reference speed
m	28,3 kg	Weight

Mounting dimensions

d _{a max}	140 mm	Maximum diameter shaft shoulder
D _{a max}	180 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum filled radius
r _{a1 max}	1 mm	Maximum filled radius



Dimensions

D ₁	144 mm	Inner diameter housing washer
B	31 mm	Height shaft washer
r _{min}	2,1 mm	Minimum chamfer dimension
r _{1 min}	1,1 mm	Minimum chamfer dimension






Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Calculation factors

A	8,2	Minimum load factor
---	-----	---------------------

Characteristics

-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed