
**FAG****7603040-TVP**

Axial angular contact ball bearing

Axial angular contact ball bearings 7603, single direction, with contact angle $\alpha = 60^\circ$, restricted tolerances

Technical information



Your current product variant

Cage	TVP	Plastic cage
Sealing	Without	
Arrangement bearing set	Standard	Single bearing
Lubricant	Without	Not greased

Main Dimensions & Performance Data

d	40 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,006 mm	Bore diameter lower tolerance
D	90 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,008 mm	Outside diameter lower tolerance
B	23 mm	Width
	0 mm	Width upper tolerance
	-0,12 mm	Width lower tolerance
C_a	52.000 N	Basic dynamic load rating, axial
C_{0a}	138.000 N	Basic static load rating, axial
C_{ua}	6.300 N	Fatigue load limit, axial
n_G Grease	4.500 1/min	Limiting speed for grease lubrication
n_g	2.600 1/min	Thermally safe operating speed
$\approx m$	0,757 kg	Weight



Mounting dimensions

D_a	75,5 mm	Diameter of housing
D_a	H12	Diameter of housing clearance
d_a	56,5 mm	Diameter shaft
d_a	h12	Diameter shaft clearance

Dimensions

r_{min}	1,5 mm	Minimum chamfer dimension
$r_{1 min}$	1,5 mm	Minimum chamfer dimension
a	68,5 mm	Distance between the apexes of the pressure cones
α	60 °	Contact angle

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.


Additional information


M_R	0,23 Nm	Bearing frictional torque
c_{aL}	1.292 N/μm	Rigidity axial
	2 μm	Axial runout
	ZM40	Recommended INA precision locknut for radial locking
	AM40	Recommended INA precision locknut for axial locking
M_A	110 Nm	Tightening torque for the recommended INA precision locknut
	25.120 N	Required locknut force axial



Characteristics

 Radial load

 Axial load in one direction

 Grease Lubrication

 Not sealed