




## ZKLN1034-2RS-PE [↗](#)

Axial angular contact ball bearing

Axial angular contact ball bearings  
ZKLN..-2RS-PE, Increased tolerances,  
double direction, lip seals on both sides

### Technical information



### Your current product variant

Sealing	2RS	Contact lip seals on both sides
Tolerance class	PE	Less stringent bearing design

### Main Dimensions & Performance Data

d	10 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,008 mm	Bore diameter lower tolerance
D	34 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,011 mm	Outside diameter lower tolerance
B	20 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C <sub>a</sub>	13.400 N	Basic dynamic load rating, axial
C <sub>0a</sub>	18.800 N	Basic static load rating, axial
C <sub>ua</sub>	850 N	Fatigue load limit, axial
n <sub>G</sub> Grease	10.900 1/min	Limiting speed for grease lubrication
n <sub>g</sub>	4.600 1/min	Thermally safe operating speed
M <sub>R</sub>	0,12 Nm	Bearing frictional torque
≈m	0,098 kg	Weight



### Mounting dimensions

$D_{a \max}$	28 mm	Maximum diameter of housing
$d_{a \min}$	14 mm	Minimum diameter shaft

### Dimensions

$d_1$	21 mm	Rib diameter inner ring
$r_{\min}$	0,3 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
$\alpha$	60 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Additional information

$c_{aL}$	325 N/μm	Rigidity axial
$c_{kL}$	25 Nm/mrad	Tilting rigidity
$M_m$	0,029 kg*cm <sup>2</sup>	Mass moment of inertia
	5 μm	Axial runout
	ZM10	Recommended INA precision locknut for radial locking
$M_A$	6 Nm	Tightening torque for the recommended INA precision locknut
	4.891 N	Required locknut force axial



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides