


**ZKLN2052-2RS-PE**

## Axial angular contact ball bearing

Axial angular contact ball bearings  
ZKLN..-2RS-PE, Increased tolerances,  
double direction, lip seals on both sides

## Technical information



## Your current product variant

|                 |     |                                 |
|-----------------|-----|---------------------------------|
| Sealing         | 2RS | Contact lip seals on both sides |
| Tolerance class | PE  | Less stringent bearing design   |

## Main Dimensions &amp; Performance Data

|                          |             |                                       |
|--------------------------|-------------|---------------------------------------|
| d                        | 20 mm       | Bore diameter                         |
|                          | 0 mm        | Bore diameter upper tolerance         |
|                          | -0,01 mm    | Bore diameter lower tolerance         |
| D                        | 52 mm       | Outside diameter                      |
|                          | 0 mm        | Outside diameter upper tolerance      |
|                          | -0,013 mm   | Outside diameter lower tolerance      |
| B                        | 28 mm       | Width                                 |
|                          | 0 mm        | Width upper tolerance                 |
|                          | -0,25 mm    | Width lower tolerance                 |
| C <sub>a</sub>           | 26.000 N    | Basic dynamic load rating, axial      |
| C <sub>0a</sub>          | 47.000 N    | Basic static load rating, axial       |
| C <sub>ua</sub>          | 2.130 N     | Fatigue load limit, axial             |
| n <sub>G</sub><br>Grease | 6.600 1/min | Limiting speed for grease lubrication |
| n <sub>g</sub>           | 3.000 1/min | Thermally safe operating speed        |
| M <sub>R</sub>           | 0,3 Nm      | Bearing frictional torque             |
| ≈m                       | 0,31 kg     | Weight                                |



### Mounting dimensions

|              |       |                             |
|--------------|-------|-----------------------------|
| $D_{a \max}$ | 43 mm | Maximum diameter of housing |
| $d_{a \min}$ | 25 mm | Minimum diameter shaft      |

### Dimensions

|              |         |                           |
|--------------|---------|---------------------------|
| $d_1$        | 34,5 mm | Rib diameter inner ring   |
| $r_{\min}$   | 0,3 mm  | Minimum chamfer dimension |
| $r_{1 \min}$ | 0,6 mm  | Minimum chamfer dimension |
| $\alpha$     | 60 °    | Contact angle             |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Additional information

|          |                          |   |
|----------|--------------------------|---|
| $c_{aL}$ | 650 N/ $\mu$ m           | Rigidity axial  |
| $c_{kL}$ | 140 Nm/mrad              | Tilting rigidity  |
| $M_m$    | 0,273 kg*cm <sup>2</sup> | Mass moment of inertia                                      |
|          | 5 $\mu$ m                | Axial runout  |
|          | ZM20                     | Recommended INA precision locknut for radial locking        |
|          | AM20                     | Recommended INA precision locknut for axial locking         |
| $M_A$    | 18 Nm                    | Tightening torque for the recommended INA precision locknut |
|          | 8.258 N                  | Required locknut force axial                                |



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides