


**ZKLN80130-2Z-XL**

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN..-2Z, double direction, gap seals on both sides

X-life

Technical information



Your current product variant

Sealing	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

Main Dimensions & Performance Data

d	80 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,008 mm	Bore diameter lower tolerance
D	130 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,015 mm	Outside diameter lower tolerance
B	45 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	100.000 N	Basic dynamic load rating, axial
C _{0a}	265.000 N	Basic static load rating, axial
C _{ua}	15.800 N	Fatigue load limit, axial
n _G Grease	3.600 1/min	Limiting speed for grease lubrication
n _g	2.700 1/min	Thermally safe operating speed
M _R	1,4 Nm	Bearing frictional torque
≈m	2,265 kg	Weight



Mounting dimensions

$D_{a \max}$	120 mm	Maximum diameter of housing
$d_{a \min}$	102 mm	Minimum diameter shaft

Dimensions

d_1	105 mm	Rib diameter inner ring
r_{\min}	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
α	60 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

c_{aL}	1.600 N/μm	Rigidity axial
c_{kL}	3.000 Nm/mrad	Tilting rigidity
M_m	27,6 kg*cm ²	Mass moment of inertia
	3 μm	Axial runout
	ZMA80/120	Recommended INA precision locknut for radial locking
	AM80	Recommended INA precision locknut for axial locking
M_A	160 Nm	Tightening torque for the recommended INA precision locknut
	20.604 N	Required locknut force axial



Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides