

**ZKLF40100-2Z-XL**

Axial angular contact ball bearing

Axial angular contact ball bearings ZKLF..-2Z, double direction, for screw mounting, gap seals on both sides

X-life




## Technical information

## Your current product variant

Sealing	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	100 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	34 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C <sub>a</sub>	47.500 N	Basic dynamic load rating, axial
C <sub>0a</sub>	101.000 N	Basic static load rating, axial
C <sub>ua</sub>	6.100 N	Fatigue load limit, axial
n <sub>G</sub> Grease	5.200 1/min	Limiting speed for grease lubrication
n <sub>g</sub>	3.300 1/min	Thermally safe operating speed
M <sub>R</sub>	0,35 Nm	Bearing frictional torque
≈m	1,468 kg	Weight





### Mounting dimensions

$D_{a \max}$	67 mm	Maximum diameter of housing
$d_{a \min}$	50 mm	Minimum diameter shaft
$t_1$	0,2 mm	Position tolerance of bore in the housing
	M8	Size of fixing screws
$n_a$	4	Number of holes in adjacent construction
$t_a$	90 °	Pitch separation angle of holes in adjacent construction
	M6	Connection thread for lubrication

### Dimensions

$d_1$	58 mm	Rib diameter inner ring
$r_{\min}$	0,3 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
J	80 mm	Pitch circle diameter fixing holes
$d_2$	8,8 mm	Fixing holes diameter
b	3 mm	Width of extraction slot
l	25 mm	Distance of extraction slot
n	8	Pitch quantity of fixing holes
t	45 °	Pitch separation angle of fixing holes
a	60 °	Contact angle

### Temperature range







$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.



### Additional information

$c_{aL}$	1.000 N/ $\mu$ m	Rigidity axial
$c_{kL}$	550 Nm/mrad	Tilting rigidity
$M_m$	2,26 kg*cm <sup>2</sup>	Mass moment of inertia
	2,5 $\mu$ m	Axial runout
	ZM40	Recommended INA precision locknut for radial locking
	AM40	Recommended INA precision locknut for axial locking
$M_A$	55 Nm	Tightening torque for the recommended INA precision locknut
	13.412 N	Required locknut force axial

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides