

**FAG****234407-M-SP**

Axial angular contact ball bearing

Axial angular contact ball bearings 2344, double direction, separable, restricted tolerances

Technical information



Your current product variant

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	62 mm	Outside diameter
B	34 mm	Width
C	17 mm	Width, outer ring
C _a	19.100 N	Basic dynamic load rating, axial
C _{0a}	46.500 N	Basic static load rating, axial
C _{ua}	4.300 N	Fatigue load limit, axial
n _G Grease	9.500 1/min	Limiting speed for grease lubrication
n _G Oil	1.400 1/min	Limiting speed for oil lubrication
m	381 g	Weight



Mounting dimensions

d_a	46,5 mm	Diameter shaft shoulder
d_a	H12	Diameter shaft shoulder clearance
D_a	57 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,15 mm	Maximum recess radius
α	60 °	Contact angle
a	103 mm	Distance between the apexes of the pressure cones

Dimensions

d_1	53 mm	Rip diameter shaft washer
B_1	8,5 mm	Height wave disc
r_{\min}	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,15 mm	Minimum chamfer dimension
d_s	3,2 mm	Diameter lubrication hole
n_s	4,8 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Additional information

c_a	316 N/μm	Axial rigidity
K_{aE}	382 N	Lift-off force
F_v	134 N	Preload force



Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed