

**FAG****234410-M-SP**

Axial angular contact ball bearing

Axial angular contact ball bearings 2344, double direction, separable, restricted tolerances

## Technical information



## Your current product variant

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP

## Main Dimensions &amp; Performance Data

d	50 mm	Bore diameter
D	80 mm	Outside diameter
B	38 mm	Width
C	19 mm	Width, outer ring
C <sub>a</sub>	27.500 N	Basic dynamic load rating, axial
C <sub>0a</sub>	79.000 N	Basic static load rating, axial
C <sub>ua</sub>	7.300 N	Fatigue load limit, axial
n <sub>G</sub> Grease	7.000 1/min	Limiting speed for grease lubrication
n <sub>G</sub> Oil	9.500 1/min	Limiting speed for oil lubrication
m	0,632 kg	Weight



### Mounting dimensions

$d_a$	62,5 mm	Diameter shaft shoulder
$d_a$	H12	Diameter shaft shoulder clearance
$D_a$	75 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,15 mm	Maximum recess radius
$\alpha$	60 °	Contact angle
$a$	133,5 mm	Distance between the apexes of the pressure cones

### Dimensions

$d_1$	70 mm	Rip diameter shaft washer
$B_1$	9,5 mm	Height wave disc
$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,15 mm	Minimum chamfer dimension
$d_s$	3,2 mm	Diameter lubrication hole
$n_s$	4,8 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Additional information

$c_a$	410 N/μm	Axial rigidity
$K_{aE}$	522 N	Lift-off force
$F_v$	183 N	Preload force



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed