


**81128-M**

Axial cylindrical roller bearing

Axial cylindrical roller bearing 811..-M, single row



Technical information



Your current product variant

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	140 mm	Bore diameter
T	31 mm	Height
C _a	236.000 N	Basic dynamic load rating, axial
C _{0a}	840.000 N	Basic static load rating, axial
C _{ua}	73.000 N	Fatigue load limit, axial
n _G	1.800 1/min	Limiting speed
n _{gr}	780 1/min	Reference speed
D	180 mm	Outside diameter
m	2,167 kg	Weight

Mounting dimensions

d _{a min}	175 mm	Minimum diameter shaft shoulder
D _{a max}	145 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum recess radius



Dimensions

D ₁	142 mm	Bore diameter housing washer
d ₁	178 mm	Rip diameter shaft washer
r _{min}	1 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81128-M	Axial roller and cage assembly
GS81128	Housing Washer
WS81128	Shaft washer
LS140180	Track Washer

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed