

**81192-M**

## Axial cylindrical roller bearing

Axial cylindrical roller bearing 811...-M, single row



## Technical information



## Your current product variant

Cage	M	Brass Cage
------	---	------------

## Main Dimensions &amp; Performance Data

d	460 mm	Bore diameter
T	80 mm	Height
C <sub>a</sub>	1.840.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	8.700.000 N	Basic static load rating, axial
C <sub>ua</sub>	670.000 N	Fatigue load limit, axial
n <sub>G</sub>	560 1/min	Limiting speed
n <sub>gr</sub>	177 1/min	Reference speed
D	560 mm	Outside diameter
m	45 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	553 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	474 mm	Maximum diameter of housing shoulder

## Dimensions

D <sub>1</sub>	464 mm	Bore diameter housing washer
d <sub>1</sub>	555 mm	Rip diameter shaft washer
r <sub>min</sub>	2,1 mm	Minimum chamfer dimension



### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Additional information

K81192-M	Axial roller and cage assembly
GS81192	Housing Washer
WS81192	Shaft washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed