

**81124-TV** [↗](#)

Axial cylindrical roller bearing

Axial cylindrical roller bearings 811, single direction, comprising K811, GS, WS



Technical information



Your current product variant

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

Main Dimensions & Performance Data

d	120 mm	Bore diameter
T	25 mm	Height
C _a	214.000 N	Basic dynamic load rating, axial
C _{0a}	760.000 N	Basic static load rating, axial
C _{ua}	67.000 N	Fatigue load limit, axial
n _G	2.090 1/min	Limiting speed
n _{gr}	780 1/min	Reference speed
D	155 mm	Outside diameter
m	1,046 kg	Weight

Mounting dimensions

d _{a min}	151 mm	Minimum diameter shaft shoulder
D _{a max}	124 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum recess radius



Dimensions

D ₁	122 mm	Bore diameter housing washer
d ₁	155 mm	Rip diameter shaft washer
r _{min}	1 mm	Minimum chamfer dimension





Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81124-TV	Axial roller and cage assembly
GS81124	Housing Washer
WS81124	Shaft washer
LS120155	Track Washer

Characteristics

	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed