

**81134-TV** [↗](#)

## Axial cylindrical roller bearing

Axial cylindrical roller bearings 811, single direction, comprising K811, GS, WS

## Technical information



## Your current product variant

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

## Main Dimensions &amp; Performance Data

d	170 mm	Bore diameter
T	34 mm	Height
C <sub>a</sub>	360.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	1.380.000 N	Basic static load rating, axial
C <sub>ua</sub>	125.000 N	Fatigue load limit, axial
n <sub>G</sub>	1.500 1/min	Limiting speed
n <sub>gr</sub>	570 1/min	Reference speed
D	215 mm	Outside diameter
≈m	2,607 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	209 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	176 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1,1 mm	Maximum recess radius

## Dimensions

D <sub>1</sub>	172 mm	Bore diameter housing washer
d <sub>1</sub>	213 mm	Rip diameter shaft washer
r <sub>min</sub>	1,1 mm	Minimum chamfer dimension



### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Additional information

K81134-TV	Axial roller and cage assembly
GS81134	Housing Washer
WS81134	Shaft washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed