

**81252-M**

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row



Technical information



Your current product variant

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	260 mm	Bore diameter
T	79 mm	Height
C _a	1.450.000 N	Basic dynamic load rating, axial
C _{0a}	5.400.000 N	Basic static load rating, axial
C _{ua}	485.000 N	Fatigue load limit, axial
n _G	930 1/min	Limiting speed
n _{gr}	310 1/min	Reference speed
D	360 mm	Outside diameter
m	25,99 kg	Weight

Mounting dimensions

d _{a min}	353 mm	Minimum diameter shaft shoulder
D _{a max}	280 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum recess radius



Dimensions

D ₁	264 mm	Bore diameter housing washer
d ₁	355 mm	Rip diameter shaft washer
r _{min}	2,1 mm	Minimum chamfer dimension






Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81252-M	Axial roller and cage assembly
GS81252	Housing Washer
WS81252	Shaft washer

Characteristics

	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing