

**81264-M**

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row

Technical information



Your current product variant

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	320 mm	Bore diameter
T	95 mm	Height
C _a	1.980.000 N	Basic dynamic load rating, axial
C _{0a}	7.600.000 N	Basic static load rating, axial
C _{ua}	650.000 N	Fatigue load limit, axial
n _G	760 1/min	Limiting speed
n _{gr}	250 1/min	Reference speed
D	440 mm	Outside diameter
≈m	46,5 kg	Weight

Mounting dimensions

d _{a min}	434 mm	Minimum diameter shaft shoulder
D _{a max}	348 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius

Dimensions

D ₁	325 mm	Bore diameter housing washer
d ₁	435 mm	Rip diameter shaft washer
r _{min}	3 mm	Minimum chamfer dimension



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

K81264-M	Axial roller and cage assembly
GS81264	Housing Washer
WS81264	Shaft washer

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed