

**81280-M**

## Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row



## Technical information



## Your current product variant

Cage	M	Brass Cage
------	---	------------

## Main Dimensions &amp; Performance Data

d	400 mm	Bore diameter
T	112 mm	Height
C <sub>a</sub>	2.850.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	11.500.000 N	Basic static load rating, axial
C <sub>ua</sub>	930.000 N	Fatigue load limit, axial
n <sub>G</sub>	610 1/min	Limiting speed
n <sub>gr</sub>	184 1/min	Reference speed
D	540 mm	Outside diameter
m	81,736 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	531 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	433 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	4 mm	Maximum recess radius



### Dimensions

D <sub>1</sub>	405 mm	Bore diameter housing washer
d <sub>1</sub>	535 mm	Rip diameter shaft washer
r <sub>min</sub>	4 mm	Minimum chamfer dimension





### Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Additional information

K81280-M	Axial roller and cage assembly
GS81280	Housing Washer
WS81280	Shaft washer

### Characteristics

-  **F<sub>a</sub>** Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed