

**81280-M**

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row



Technical information



Your current product variant

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	400 mm	Bore diameter
T	112 mm	Height
C _a	2.850.000 N	Basic dynamic load rating, axial
C _{0a}	11.500.000 N	Basic static load rating, axial
C _{ua}	930.000 N	Fatigue load limit, axial
n _G	610 1/min	Limiting speed
n _{gr}	184 1/min	Reference speed
D	540 mm	Outside diameter
m	81,736 kg	Weight

Mounting dimensions

d _{a min}	531 mm	Minimum diameter shaft shoulder
D _{a max}	433 mm	Maximum diameter of housing shoulder
r _{a max}	4 mm	Maximum recess radius



Dimensions

D ₁	405 mm	Bore diameter housing washer
d ₁	535 mm	Rip diameter shaft washer
r _{min}	4 mm	Minimum chamfer dimension


Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81280-M	Axial roller and cage assembly
GS81280	Housing Washer
WS81280	Shaft washer

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed