


**811/630-M**

Axial cylindrical roller bearing

Axial cylindrical roller bearing 811..-M, single row



## Technical information



## Your current product variant

Cage	M	Brass Cage
------	---	------------

## Main Dimensions &amp; Performance Data

d	630 mm	Bore diameter
T	95 mm	Height
C <sub>a</sub>	2.460.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	12.200.000 N	Basic static load rating, axial
C <sub>ua</sub>	870.000 N	Fatigue load limit, axial
n <sub>G</sub>	415 1/min	Limiting speed
n <sub>gr</sub>	139 1/min	Reference speed
D	750 mm	Outside diameter
m	83,27 kg	Weight

## Mounting dimensions

r <sub>a max</sub>	3 mm	Maximum recess radius
--------------------	------	-----------------------

## Dimensions

D <sub>1</sub>	635 mm	Bore diameter housing washer
d <sub>1</sub>	745 mm	Rip diameter shaft washer
r <sub>min</sub>	3 mm	Minimum chamfer dimension



### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Additional information

K811/630-M	Axial roller and cage assembly
GS811/630	Housing Washer
WS811/630	Shaft washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed