

**81206-L**

## Axial cylindrical roller bearing

Axial cyl roller and cage assy -LS K812...-L,  
single row

## Technical information



## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
T	16 mm	Height
C <sub>a</sub>	64.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	141.000 N	Basic static load rating, axial
C <sub>ua</sub>	14.400 N	Fatigue load limit, axial
n <sub>G</sub>	7.000 1/min	Limiting speed
n <sub>gr</sub>	2.650 1/min	Reference speed
D	52 mm	Outside diameter
≈m	127,6 g	Weight

## Mounting dimensions

d <sub>a min</sub>	50 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	31 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	0,6 mm	Maximum recess radius

## Dimensions

D <sub>1</sub>	32 mm	Bore diameter housing washer
d <sub>1</sub>	52 mm	Rip diameter shaft washer
r <sub>min</sub>	0,6 mm	Minimum chamfer dimension







### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Additional information

K81206-L	Axial roller and cage assembly
GS81206	Housing Washer
WS81206	Shaft washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed