


**89315-M**

## Axial cylindrical roller bearing

Axial cylindrical roller bearing 893..-M, two-row

## Technical information



## Your current product variant

Cage	M	Brass Cage
------	---	------------

## Main Dimensions &amp; Performance Data

d	75 mm	Bore diameter
D	135 mm	Outside diameter
T	36 mm	Height
C <sub>a</sub>	275.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	960.000 N	Basic static load rating, axial
C <sub>ua</sub>	88.000 N	Fatigue load limit, axial
n <sub>G</sub>	2.700 1/min	Limiting speed
n <sub>gr</sub>	1.110 1/min	Reference speed
≈m	2,57 kg	Weight

## Mounting dimensions

d <sub>a</sub>	132 mm	Minimum diameter shaft shoulder
D <sub>a</sub>	81 mm	Maximum diameter of housing shoulder
r <sub>a</sub>	1,5 mm	Recess radius



### Dimensions

D <sub>1</sub>	77 mm	Bore diameter housing washer
d <sub>1</sub>	135 mm	Rip diameter shaft washer
B	12,5 mm	Width
r <sub>min</sub>	1,5 mm	Minimum chamfer dimension
D <sub>c1</sub>	75 mm	Cage bore diameter


### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Additional information

K89315-M	Axial roller and cage assembly
GS89315	Housing Washer
WS89315	Shaft washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed