



**89311-TV** [↗](#)

Axial cylindrical roller bearing

Axial cylindrical roller bearings 893, single direction, comprising K893, GS, WS



Technical information

**Your current product variant**

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	105 mm	Outside diameter
T	30 mm	Height
C_a	184.000 N	Basic dynamic load rating, axial
C_{0a}	600.000 N	Basic static load rating, axial
C_{ua}	53.000 N	Fatigue load limit, axial
n_G	3.600 1/min	Limiting speed
n_{gr}	1.490 1/min	Reference speed
m	1,17 kg	Weight

Mounting dimensions

d_a	103 mm	Minimum diameter shaft shoulder
D_a	61 mm	Maximum diameter of housing shoulder
r_a	1,1 mm	Recess radius



Dimensions

D ₁	57 mm	Bore diameter housing washer
d ₁	105 mm	Rip diameter shaft washer
B	30 mm	Width
r _{min}	1,1 mm	Minimum chamfer dimension
D _{c1}	55 mm	Cage bore diameter





Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K89311-TV	Axial roller and cage assembly
GS89311	Housing Washer
WS89311	Shaft washer

Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed