


**89418-M**

## Axial cylindrical roller bearing

Axial cylindrical roller bearings 894, single direction, comprising K894, GS, WS

## Technical information

**Main Dimensions & Performance Data**

d	90 mm	Bore diameter
D	190 mm	Outside diameter
T	60 mm	Height
C <sub>a</sub>	680.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	2.200.000 N	Basic static load rating, axial
C <sub>ua</sub>	225.000 N	Fatigue load limit, axial
n <sub>G</sub>	2.060 1/min	Limiting speed
n <sub>gr</sub>	850 1/min	Reference speed
m	9,396 kg	Weight

**Dimensions**

D <sub>1</sub>	93 mm	Bore diameter housing washer
d <sub>1</sub>	190 mm	Rip diameter shaft washer
r <sub>min</sub>	2,1 mm	Minimum chamfer dimension

**Temperature range**

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.



### Additional information

---

K89418-M	Axial roller and cage assembly
GS89418	Housing Washer
WS89418	Shaft washer

### Characteristics

---

 Axial load in one direction

 Grease Lubrication

 Oil Lubrication

 Not sealed