

**FAG****29248-E1-MB** [↗](#)

Axial spherical roller bearing

Axial spherical roller bearing 292...E1-MB,
with flanging ring

Technical information



Your current product variant

Heat treatment	Standard	Standard
Cage	MB	Solid brass cage
Locating feature, housing washer	Without	
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	340 mm	Outside diameter
T	60 mm	Section height
C _a	1.010.000 N	Basic dynamic load rating, axial
C _{0a}	4.150.000 N	Basic static load rating, axial
C _{ua}	470.000 N	Fatigue load limit, axial
n _G	1.890 1/min	Limiting speed
n _{gr}	1.060 1/min	Reference speed
≈m	16,913 kg	Weight



Mounting dimensions

$d_{a \min}$	290 mm	Minimum diameter shaft shoulder
$D_{a \max}$	311 mm	Maximum diameter of housing shoulder
$D_{b \min}$	344 mm	Minimum bore diameter housing
$d_{b \max}$	250 mm	Maximum distance sleeve
$r_{a \max}$	2,1 mm	Maximum recess radius

Dimensions

D_1	283 mm	Bore diameter housing washer
d_1	320 mm	Rip diameter shaft washer
r_{\min}	2,1 mm	Minimum chamfer dimension
T_1	30 mm	Height of the housing washer
T_2	22 mm	Height of shaft washer
T_3	37 mm	Height of the shaft washer
T_4	57 mm	Height of shaft washer, inc. lip ring
A	130 mm	Distance of the center point

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment