


**FAG****29284-E1-N1-MB** [↗](#)

Axial spherical roller bearing

Axial spherical roller bearing 292...-E1-MB,
with flanging ring

Technical information



Your current product variant

Heat treatment	Standard	Standard
Cage	MB	Solid brass cage
Locating feature, housing washer	N1	Locating feature, housing washer
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	420 mm	Bore diameter
D	580 mm	Outside diameter
T	95 mm	Section height
C _a	2.460.000 N	Basic dynamic load rating, axial
C _{0a}	11.100.000 N	Basic static load rating, axial
C _{ua}	1.130.000 N	Fatigue load limit, axial
n _G	1.040 1/min	Limiting speed
n _{gr}	600 1/min	Reference speed
≈m	74,22 kg	Weight



Mounting dimensions

$d_{a \min}$	495 mm	Minimum diameter shaft shoulder
$D_{a \max}$	534 mm	Maximum diameter of housing shoulder
$D_{b \min}$	590 mm	Minimum bore diameter housing
$d_{b \max}$	439 mm	Maximum distance sleeve
$r_{a \max}$	4 mm	Maximum recess radius

Dimensions

D_1	489 mm	Bore diameter housing washer
d_1	545 mm	Rip diameter shaft washer
r_{\min}	5 mm	Minimum chamfer dimension
T_1	46 mm	Height of the housing washer
T_2	34 mm	Height of shaft washer
T_3	58,5 mm	Height of the shaft washer
T_4	91 mm	Height of shaft washer, inc. lip ring
A	225 mm	Distance of the center point

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.



Characteristics



Radial load



Axial load in one direction



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment