

**FAG****29288-E1-MB** [↗](#)

Axial spherical roller bearing

Axial spherical roller bearing 292...E1-MB,
with flanging ring

Technical information



Your current product variant

Heat treatment	Standard	Standard
Cage	MB	Solid brass cage
Locating feature, housing washer	Without	
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	440 mm	Bore diameter
D	600 mm	Outside diameter
T	95 mm	Section height
C _a	2.500.000 N	Basic dynamic load rating, axial
C _{0a}	12.400.000 N	Basic static load rating, axial
C _{ua}	1.200.000 N	Fatigue load limit, axial
n _G	1.010 1/min	Limiting speed
n _{gr}	560 1/min	Reference speed
≈m	90,76 kg	Weight



Mounting dimensions

$d_{a \min}$	520 mm	Minimum diameter shaft shoulder
$D_{a \max}$	554 mm	Maximum diameter of housing shoulder
$D_{b \min}$	610 mm	Minimum bore diameter housing
$d_{b \max}$	458 mm	Maximum distance sleeve
$r_{a \max}$	4 mm	Maximum recess radius

Dimensions

D_1	508 mm	Bore diameter housing washer
d_1	570 mm	Rip diameter shaft washer
r_{\min}	5 mm	Minimum chamfer dimension
T_1	49 mm	Height of the housing washer
T_2	34 mm	Height of shaft washer
T_3	61 mm	Height of the shaft washer
T_4	91 mm	Height of shaft washer, inc. lip ring
A	235 mm	Distance of the center point

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment