



FAG

293/800-E1-XL-MB

Axial spherical roller bearing

Axial spherical roller bearing 293..-E1-XL-MB,
with flanging ring

X-life

Technical information



Your current product variant

Heat treatment	Standard	Standard
Cage	MB	Solid brass cage
Locating feature, housing washer	Without	
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	800 mm	Bore diameter
D	1.180 mm	Outside diameter
T	230 mm	Section height
C _a	13.500.000 N	Basic dynamic load rating, axial
C _{0a}	54.000.000 N	Basic static load rating, axial
C _{ua}	4.900.000 N	Fatigue load limit, axial
n _G	485 1/min	Limiting speed
n _{gr}	237 1/min	Reference speed
≈m	817,5 kg	Weight



Mounting dimensions

$d_{a \min}$	980 mm	Minimum diameter shaft shoulder
$D_{a \max}$	1.070 mm	Maximum diameter of housing shoulder
$D_{b \min}$	1.202 mm	Minimum bore diameter housing
$d_{b \max}$	840 mm	Maximum distance sleeve
$r_{a \max}$	8 mm	Maximum recess radius

Dimensions

D_1	965 mm	Bore diameter housing washer
d_1	1.100 mm	Rip diameter shaft washer
r_{\min}	9,5 mm	Minimum chamfer dimension
T_1	111 mm	Height of the housing washer
T_2	83 mm	Height of shaft washer
T_3	145,5 mm	Height of the shaft washer
T_4	222 mm	Height of shaft washer, inc. lip ring
A	440 mm	Distance of the center point

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment