



**FAG****29384-E1-XL-MB**

Axial spherical roller bearing

Axial spherical roller bearing 293..-E1-XL-MB,  
with flanging ring**X-life**

## Technical information

**Your current product variant**

Heat treatment	Standard	Standard
Cage	MB	Solid brass cage
Locating feature, housing washer	Without	
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

**Main Dimensions & Performance Data**

d	420 mm	Bore diameter
D	650 mm	Outside diameter
T	140 mm	Section height
$C_a$	5.000.000 N	Basic dynamic load rating, axial
$C_{0a}$	17.500.000 N	Basic static load rating, axial
$C_{ua}$	1.850.000 N	Fatigue load limit, axial
$n_G$	940 1/min	Limiting speed
$n_{gr}$	480 1/min	Reference speed
$m$	162,5 kg	Weight



### Mounting dimensions

$d_{a \min}$	530 mm	Minimum diameter shaft shoulder
$D_{a \max}$	585 mm	Maximum diameter of housing shoulder
$D_{b \min}$	664 mm	Minimum bore diameter housing
$d_{b \max}$	449 mm	Maximum distance sleeve
$r_{a \max}$	5 mm	Maximum recess radius

### Dimensions

$D_1$	520 mm	Bore diameter housing washer
$d_1$	600 mm	Rip diameter shaft washer
$r_{\min}$	6 mm	Minimum chamfer dimension
$T_1$	67,5 mm	Height of the housing washer
$T_2$	50 mm	Height of shaft washer
$T_3$	85 mm	Height of the shaft washer
$T_4$	135 mm	Height of shaft washer, inc. lip ring
A	235 mm	Distance of the center point

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Axial load in one direction



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment