


**FAG****29480-E1-XL-MB**

Axial spherical roller bearing

Axial spherical roller bearing 294..-E1-XL-MB,  
with flanging ring**X-life**

## Technical information

**Your current product variant**

Heat treatment	Standard	Standard
Cage	MB	Solid brass cage
Locating feature, housing washer	Without	
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

**Main Dimensions & Performance Data**

d	400 mm	Bore diameter
D	710 mm	Outside diameter
T	185 mm	Section height
C <sub>a</sub>	8.200.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	26.500.000 N	Basic static load rating, axial
C <sub>ua</sub>	2.440.000 N	Fatigue load limit, axial
n <sub>G</sub>	870 1/min	Limiting speed
n <sub>gr</sub>	425 1/min	Reference speed
≈m	304 kg	Weight



### Mounting dimensions

$d_{a \min}$	555 mm	Minimum diameter shaft shoulder
$D_{a \max}$	622 mm	Maximum diameter of housing shoulder
$D_{b \min}$	722 mm	Minimum bore diameter housing
$d_{b \max}$	434 mm	Maximum distance sleeve
$r_{a \max}$	6 mm	Maximum recess radius

### Dimensions

$D_1$	525 mm	Bore diameter housing washer
$d_1$	650 mm	Rip diameter shaft washer
$r_{\min}$	7,5 mm	Minimum chamfer dimension
$T_1$	89,5 mm	Height of the housing washer
$T_2$	69 mm	Height of shaft washer
$T_3$	120 mm	Height of the shaft washer
$T_4$	178 mm	Height of shaft washer, inc. lip ring
A	234 mm	Distance of the center point

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.



## Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment