



FAG

29332-E1-XL-N1

Axial spherical roller bearing

Axial spherical roller bearing 293..-E1-XL, no flanging ring

X-life

Technical information



Your current product variant

Heat treatment	Standard	Standard
Locating feature, housing washer	N1	Locating feature, housing washer
Cage	JP	Sheet metal cage
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	270 mm	Outside diameter
T	67 mm	Height
C _a	1.220.000 N	Basic dynamic load rating, axial
C _{0a}	3.550.000 N	Basic static load rating, axial
C _{ua}	445.000 N	Fatigue load limit, axial
n _G	2.500 1/min	Limiting speed
n _{gr}	1.320 1/min	Reference speed
≈m	13,64 kg	Weight



Mounting dimensions

$d_{a \min}$	215 mm	Minimum diameter shaft shoulder
$D_{a \max}$	236 mm	Maximum diameter of housing shoulder
$D_{b \min}$	274 mm	Minimum bore diameter housing
$d_{b \max}$	176 mm	Maximum distance sleeve
$d_{b1 \max}$	170 mm	Maximum chamfer diameter of distance sleeve
$r_{a \max}$	2,5 mm	Maximum recess radius
	30 °	Angle of chamfer of the distance sleeve

Dimensions

D_1	203 mm	Bore diameter housing washer
d_1	248 mm	Rip diameter shaft washer
r_{\min}	3 mm	Minimum chamfer dimension
T_1	33 mm	Height of the housing washer
T_3	42 mm	Height of the shaft washer
T_5	59,5 mm	Distance shaft washer - cage
A	92 mm	Distance of the center point

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.



Characteristics



Radial load



Axial load in one direction



Grease Lubrication



Oil Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment