



FAG

29415-E1-XL-N1

Axial spherical roller bearing

Axial spherical roller bearing 294..-E1-XL, no flanging ring

X-life

Technical information



Your current product variant

Heat treatment	Standard	Standard
Locating feature, housing washer	N1	Locating feature, housing washer
Cage	JP	Sheet metal cage
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	160 mm	Outside diameter
T	51 mm	Height
C _a	650.000 N	Basic dynamic load rating, axial
C _{0a}	1.540.000 N	Basic static load rating, axial
C _{ua}	179.000 N	Fatigue load limit, axial
n _G	4.700 1/min	Limiting speed
n _{gr}	2.260 1/min	Reference speed
≈m	4,4 kg	Weight



Mounting dimensions

$d_{a \min}$	115 mm	Minimum diameter shaft shoulder
$D_{a \max}$	132 mm	Maximum diameter of housing shoulder
$D_{b \min}$	163 mm	Minimum bore diameter housing
$d_{b \max}$	82,5 mm	Maximum distance sleeve
$r_{a \max}$	2 mm	Maximum recess radius








Dimensions

D_1	105,5 mm	Bore diameter housing washer
d_1	142,3 mm	Rip diameter shaft washer
r_{\min}	2 mm	Minimum chamfer dimension
T_1	24,5 mm	Height of the housing washer
T_3	33,5 mm	Height of the shaft washer
T_5	46 mm	Distance shaft washer - cage
A	47 mm	Distance of the center point

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment
	Dynamic angular error and misalignment