



FAG

29436-E1-XL-N1

Axial spherical roller bearing

Axial spherical roller bearing 294..-E1-XL, no flanging ring

X-life

Technical information



Your current product variant

Heat treatment	Standard	Standard
Locating feature, housing washer	N1	Locating feature, housing washer
Cage	JP	Sheet metal cage
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	360 mm	Outside diameter
T	109 mm	Height
C _a	2.850.000 N	Basic dynamic load rating, axial
C _{0a}	7.700.000 N	Basic static load rating, axial
C _{ua}	770.000 N	Fatigue load limit, axial
n _G	1.860 1/min	Limiting speed
n _{gr}	940 1/min	Reference speed
≈m	45,2 kg	Weight



Mounting dimensions

$d_{a \min}$	265 mm	Minimum diameter shaft shoulder
$D_{a \max}$	305 mm	Maximum diameter of housing shoulder
$D_{b \min}$	366 mm	Minimum bore diameter housing
$d_{b \max}$	210 mm	Maximum distance sleeve
$d_{b1 \max}$	197 mm	Maximum chamfer diameter of distance sleeve
$r_{a \max}$	4 mm	Maximum recess radius
	30 °	Angle of chamfer of the distance sleeve

Dimensions

D_1	250 mm	Bore diameter housing washer
d_1	315,5 mm	Rip diameter shaft washer
r_{\min}	5 mm	Minimum chamfer dimension
T_1	53 mm	Height of the housing washer
T_3	69,5 mm	Height of the shaft washer
T_5	96 mm	Distance shaft washer - cage
A	110 mm	Distance of the center point

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.



Characteristics



Radial load



Axial load in one direction



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment