
**NKX30-XL**

Needle roller/axial ball bearing

Needle roller/axial ball bearings NKX, axial component, single direction, to DIN 5429, without end cap, for oil lubrication

X-life

Technical information



Your current product variant

Sealing	Without
Cage	Standard

Main Dimensions & Performance Data

F_w	30 mm	Bore diameter
D	42 mm	Outside diameter
C	30 mm	Height
C_r	25.500 N	Basic dynamic load rating, radial
C_{0r}	36.000 N	Basic static load rating, radial
C_a	20.400 N	Basic dynamic load rating, axial
C_{0a}	42.000 N	Basic static load rating, axial
C_{ur}	6.400 N	Fatigue load limit, radial
C_{ua}	2.090 N	Fatigue load limit, axial
n_G	5.000 1/min	Limiting speed
$\approx m$	136,85 g	Weight

Mounting dimensions

d_a	42,7 mm	Mounting dimension shaft shoulder
$r_{a \max}$	0,6 mm	Maximum recess radius



Dimensions

D 1 max	47,1 mm	Maximum outside diameter flange
D 2 max	47,1 mm	Maximum outside diameter flange
C 1	11 mm	Width of the axial bearing component
C 1	9,5 mm	Distance to lubrication hole
C 2	9,5 mm	Distance to lubrication hole
d _w	30 mm	Bore diameter of shaft washer
r _{min}	0,6 mm	Minimum chamfer dimension

Temperature range






T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

IR25X30X20-XL

Suitable inner rings IR

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed