


**NKX50-Z-XL**

## Needle roller/axial ball bearing

Needle roller/axial ball bearings NKX...-Z, axial component, single direction, to DIN 5429, with end cap, for grease lubrication

X-life

## Technical information



## Your current product variant

Type of Seal	Z	Bearing with end cap
Cage	Standard	

## Main Dimensions &amp; Performance Data

$F_w$	50 mm	Bore diameter
D	62 mm	Outside diameter
C	35 mm	Height
$C_r$	43.000 N	Basic dynamic load rating, radial
$C_{0r}$	74.000 N	Basic static load rating, radial
$C_a$	29.000 N	Basic dynamic load rating, axial
$C_{0a}$	75.000 N	Basic static load rating, axial
$C_{ur}$	12.900 N	Fatigue load limit, radial
$C_{ua}$	3.750 N	Fatigue load limit, axial
$n_G$	3.300 1/min	Limiting speed
$\approx m$	288,35 g	Weight

## Mounting dimensions

$d_a$	65,5 mm	Mounting dimension shaft shoulder
$r_{a \max}$	0,6 mm	Maximum recess radius



## Dimensions

D 1 max	71,5 mm	Maximum outside diameter flange
D 2 max	71,5 mm	Maximum outside diameter flange
C 1	14 mm	Width of the axial bearing component
C 1	10 mm	Distance to lubrication hole
C 2	10 mm	Distance to lubrication hole
d w	50 mm	Bore diameter of shaft washer
r min	0,6 mm	Minimum chamfer dimension

## Temperature range





T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

## Additional information

IR45X50X25-XL

Suitable inner rings IR

## Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Sealed on one side