

**YRTC580-XL**

Axial/radial roller bearing

Axial/radial bearings, double direction, for screw mounting



X-life

Technical information

**Main Dimensions & Performance Data**

d	580 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,025 mm	Bore diameter lower tolerance
D	750 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,035 mm	Outside diameter lower tolerance
H	90 mm	Height
C_r	235.000 N	Basic dynamic load rating, radial
C_{0r}	730.000 N	Basic static load rating, radial
C_a	580.000 N	Basic dynamic load rating, axial
C_{0a}	4.450.000 N	Basic static load rating, axial
n_G	80 1/min	Limiting speed
M_R	60 Nm	Bearing friction torque at 5 1/min
$\approx m$	85,2 kg	Weight



Mounting dimensions

J	610 mm	Pitch circle diameter fixing holes in inner ring
J ₁	720 mm	Pitch circle diameter fixing holes in outer ring
d ₁	11,4 mm	Fixing holes diameter inner ring
d ₂	18 mm	Counterbore diameter of fixing holes
a	11 mm	Counterbore depth of fixing holes
	46	Quantity of fixing holes inner ring
d ₃	11,4 mm	Fixing holes diameter outer ring
	42	Quantity of fixing holes outer ring
n	48	Pitch quantity
t	7,5 °	Pitch separation angle
G	M12	Threaded extraction hole
	6	Quantity of threaded extraction hole
M _A	68 Nm	Screw tightening torque
	2	Quantity of retaining screws
t ₁	10 µm	Axial and radial runout, measurement standard; Measured on mounted bearing, with ideal adjacent construction.

Dimensions

H ₁	60 mm	Height contact face outer ring
	0,25 mm	Height contact face outerring H1 upper tolerance
	-0,25 mm	Height contact face outerring H1 lower tolerance
H ₂	30 mm	Height contact face outer ring
	0,25 mm	Height contact face outerring H2 upper tolerance
	-0,25 mm	Height contact face outerring H2 lower tolerance
D _{1 max}	700 mm	Maximum diameter inner ring
C	30 mm	Width of outer ring










Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

c_{aL}	23.800 N/ μ m	Axial rigidity of bearing position
c_{rL}	11.600 N/ μ m	Radial rigidity of bearing position
c_{kL}	1.176.000 Nm/mrad	Tilting rigidity of bearing position
c_{aW}	41.800 N/ μ m	Axial rigidity of rolling element set
c_{rW}	12.500 N/ μ m	Radial rigidity of rolling element set
c_{kW}	1.960.000 Nm/mrad	Tilting rigidity of rolling element set

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Moments about all axes
-  Grease Lubrication
-  Not sealed
-  Large bearing