

**SX011824-A-RR**

Crossed roller bearing

Crossed roller bearingsdimension series 18 to
DIN 616

Technical information



Your current product variant

Coating	RR	Protected against corrosion by Corrotect special coating
---------	----	--

Main Dimensions & Performance Data

d ₁	120 mm	Bore Diameter
	0,004 mm	Bore diameter upper tolerance
	-0,018 mm	Bore diameter lower tolerance
D _a	150 mm	Outside Diameter
	0 mm	Outside diameter upper tolerance
	-0,025 mm	Outside diameter lower tolerance
H	16 mm	Height of the assembled bearing
h _i	16 mm	Height inner ring
	0,06 mm	Width upper tolerance
	-0,06 mm	Width lower tolerance
≈m	0,72 kg	Weight



Dimensions

D_i	135,6 mm	Inner diameter outer ring
D_M	135 mm	Rolling element pitch circle diameter
d_a	134,4 mm	Outer diameter inner ring
h	16 mm	Height of individual ring
	0 mm	Height of individual ring upper tolerance
	-0,01 mm	Height of individual ring lower tolerance
r_{min}	1 mm	Chamfer dimension
S	1,5 mm	Diameter of lubrication hole

Temperature range








T_{min}	-30 °C	Operating temperature min.
T_{max}	80 °C	Operating temperature max.



Calculation factors

	0,01 mm	Running accuracy, radial
	0,01 mm	Running accuracy, axial
$S_{r \min}$	0,005 mm	Minimum radial bearing clearance, at standard bearing clearance
$S_{r \max}$	0,02 mm	Maximum radial bearing clearance, at standard bearing clearance
$S_{k \min}$	0,01 mm	Minimum axial tilting clearance, at standard bearing clearance
$S_{k \max}$	0,04 mm	Maximum axial tilting clearance, at standard bearing clearance
C_a	39.500 N	Basic dynamic load rating, axial
C_{0a}	140.000 N	Basic static load rating, axial
C_r	28.000 N	Basic dynamic load rating, radial (for radial load only)
C_{0r}	69.000 N	Basic static load rating, radial (for radial load only)
$N_{G \text{ oil}}$	1.130 1/min	Limiting speed for oil lubrication with normal clearance
N_G Grease	565 1/min	Limiting speed for grease lubrication with normal clearance
	61824	Dimensions identical to ISO dimension series 18

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Small design envelope