


**SX011828-A-R+4/-8** [↗](#)

Crossed roller bearing

Crossed roller bearings dimension series 18 to
DIN 616

Technical information



Your current product variant

Preload	R+4/-8	Equals RL0 standard
---------	--------	---------------------

Main Dimensions & Performance Data

d ₁	140 mm	Bore Diameter
	0,004 mm	Bore diameter upper tolerance
	-0,021 mm	Bore diameter lower tolerance
D _a	175 mm	Outside Diameter
	0 mm	Outside diameter upper tolerance
	-0,025 mm	Outside diameter lower tolerance
H	18 mm	Height of the assembled bearing
h _i	18 mm	Height inner ring
	0,06 mm	Width upper tolerance
	-0,06 mm	Width lower tolerance
≈m	1,095 kg	Weight



Dimensions

D_i	157,7 mm	Inner diameter outer ring
D_M	157 mm	Rolling element pitch circle diameter
d_a	156,3 mm	Outer diameter inner ring
h	18 mm	Height of individual ring
	0 mm	Height of individual ring upper tolerance
	-0,01 mm	Height of individual ring lower tolerance
r_{min}	1,1 mm	Chamfer dimension
S	1,5 mm	Diameter of lubrication hole

Temperature range








T_{min}	-30 °C	Operating temperature min.
T_{max}	80 °C	Operating temperature max.

Calculation factors

	0,015 mm	Running accuracy, radial
	0,01 mm	Running accuracy, axial
RLO_{max}	0,004 mm	Low clearance: Radial clearance
RLO_{max}	0,008 mm	Low clearance: Preload
C_a	64.000 N	Basic dynamic load rating, axial
C_{0a}	223.000 N	Basic static load rating, axial
C_r	45.500 N	Basic dynamic load rating, radial (for radial load only)
C_{0r}	109.000 N	Basic static load rating, radial (for radial load only)
$N_{G\ oil}$	975 1/min	Limiting speed for oil lubrication with normal clearance
N_G Grease	485 1/min	Limiting speed for grease lubrication with normal clearance
$N_{G\ oil}$	485 1/min	Limiting speed for oil lubrication with preload
N_G Grease	240 1/min	Limiting speed for grease lubrication with preload
	61828	Dimensions identical to ISO dimension series 18



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope